

PAT-NO: JP403040771A
DOCUMENT-IDENTIFIER: JP 03040771 A
TITLE: ULTRASONIC MOTOR
PUBN-DATE: February 21, 1991

INVENTOR-INFORMATION:

NAME

UCHIKAWA, TADAYASU

ONISHI, OSAMU

MYOGA, OSAMU

INOUE, TAKESHI

ASSIGNEE-INFORMATION:

NAME

NEC CORP

COUNTRY

N/A

APPL-NO: JP01176511

APPL-DATE: July 6, 1989

INT-CL (IPC): H02N002/00

US-CL-CURRENT: 310/333

ABSTRACT:

PURPOSE: To enhance the efficiency of an ultrasonic motor by employing a plurality of materials having different densities as materials used for a head mass part of a stator to optimize it, and bringing vertical resonance into coincidence with torsional resonance.

CONSTITUTION: A wear resistant material 24 is adhered to a rotor 19. When a voltage is applied to a vertical piezoelectric element 13 and a torsional piezoelectric element 14, phase difference of voltages is suitably regulated, and vertical resonance frequency is brought into coincidence with

torsional
resonance frequency at the time of high power excitation, the
resonances are
combined by vertical and torsional amplitudes in a boundary between a
stator 18
and a rotor 19 to cause a strong elliptical vibration. Since head
masses 1, 2
made of materials having different densities do not have so high
stiffness,
they do not contribute to variation in the resonance frequency of the
vertical
vibration, but act as large inertial mass with respect to the
torsional
vibration. Accordingly, the resonance frequency of the torsional
vibration is
remarkably lowered.

COPYRIGHT: (C)1991,JPO&Japio